

NOTES:

- 1. METER SETTING NOT TO OBSTRUCTED IN ANYWAY.
- 2. ALL FITTINGS IN THE METER SPREAD SHALL BE BRASS I.P.T.
- 3. BACKFLOW PREVENTION DEVICE (RPZ) INSTALLED AND MAINTAINED BY OWNER. RPZ MUST BE TESTED ANNUALLY AND REPORT FORM MUST BE SUBMITTED TO MOON TOWNSHIP MUNICIPAL AUTHORITY.
- 4. RPZ MUST EITHER BE INSTALLED AHEAD OF DEDUCT METER, PIPED TO FLOOR DRAIN OR INSTALLED IMMEDIATELY OUTSIDE OF STRUCTURE IN A HOT BOX.
- 5. PROVIDE PROPER DRAIN AT METER SETTING.
- 6. DEDUCT METER CANNOT BE INSTALLED MORE THAN 5 FT. FROM FLOOR WITHOUT PRIOR AUTHORITY APPROVAL.

- 7. DEDUCT METER IS INSTALLED, OWNED AND MAINTAINED BY CUSTOMER. DEDUCT METER MUST BE AUTHORITY APPROVED.
- 8. DEDUCT METER SHALL BE EQUIPPED WITH AN EXTERIOR REMOTE READER. THIS REMOTE READER SHALL BE INSTALLED WITHIN ONE (1) FOOT OF THE EXISTING WATER METER REMOTE READER.
- 9. THE DEDUCT METER IS ONLY PERMITTED TO FEED OUTSIDE FIXTURES THAT DO NOT DRAIN TO THE SANITARY SEWER.
- 10. A STRAINER AND REGULATOR AHEAD OF THE DEDUCT METER IS ADVISABLE. CONSULT MANUFACTURER'S RECOMMENDATIONS.
- 11. DEDUCT METER SHALL BE EITHER SENSUS IPERL OR NEPTUNE MODEL T-10.

MOON TOWNSHIP MUNICIPAL AUTHORITY ALLEGHENY COUNTY PENNSYLVANIA		WATER DISTRIBUTION SYSTEM RESIDENTIAL DEDUCT METER
Not to scale	November 2013	Standard Detail SD-037